

FIREBRAKE

FLAME RETARDANT LOW SMOKE BUILDING WIRES



ISO
9001:2008

ISO
14001:2004

OHSAS
18001:2007

IS:694




Extra Assurance,
Extra Safe



POLYCAB

Satish Enterprise Pvt. Ltd.

Authorised Distributors



Sales Off:

304, Elphinstone House,
Opp. Sterling Cinema,
17, Murzban Road,
Mumbai - 400 001
022 2207 8520 / 6434/ 35
99207 23289
022 2207 1469
office@satishent.com /
satishent@mtnl.net.in

E-mail:

FRLS BUILDING WIRES

POLYCAB FLAME RETARDANT LOW SMOKE (FRLS) PVC INSULATED BUILDING WIRES

These wires are now being preferred over the FR wires in residential and commercial buildings due to reduced smoke generation. Polycab FRLS Wires have enhanced properties of PVC insulation to reduce the toxic smoke generated in case of fire. Modern households and offices have increased number of gadgets. This concentrated load increases the chances to fire due to overload and subsequent short circuit. Since fires are generally attributed to electrical short circuits, due care should be taken in selection and installation of low and non-toxic smoke generating wires and cables for highly populated buildings.

Polycab FRLS Building Wires are premium quality wires with Flame Retardant Low Smoke properties. Oxygen Index of normal PVC Wires is about 25% while Polycab FRLS Building Wires have Oxygen Index of more than the minimum 29%. Low Smoke Density of 60% helps in facilitating faster evacuation and fire fighting activities.

These wires are recommended for all premium quality construction like hotels, hospitals, schools, commercial complexes, residential apartments and so on.

UNIQUE PROCESS FEATURES

- On-line wire drawing and annealing.
- High speed extruders (upto 500 metres per minute).
- Twin PVC insulated for better insulation & electrical properties.
- Automatic on-line critical diameter control.
- Stringent quality control.

POLYCAB 1100V

| SINGLE CORE, TWIN INSULATED WIRES IN VOLTAGE GRADE 1100 V. | | | | | |
|--|--------------------------|--------------------------------|--------------------------|-----------------------------------|----------------------------------|
| Nominal area of Conductor | Number/Nom. Dia. of wire | Thickness of Insulation (Nom.) | Approx. overall Diameter | Current carrying capacity* Rating | Resistance (Max.) per Km. @ 20°C |
| Sq. mm. | mm. | mm. | mm. | Amps. | Ohms |
| 1.0 | 14/0.3 | 0.7 | 2.65 | 12 | 18.10 |
| 1.5 | 22/0.3 | 0.7 | 2.95 | 16 | 12.10 |
| 2.5 | 36/0.3 | 0.8 | 3.55 | 22 | 7.41 |
| 4.0 | 56/0.3 | 0.8 | 4.0 | 29 | 4.95 |
| 6.0 | 84/0.3 | 0.8 | 4.6 | 37 | 3.30 |
| 10.0 | 80/0.4 | 1.0 | 5.8 | 51 | 1.91 |
| 16.0 | 126/0.4 | 1.0 | 6.8 | 68 | 1.21 |

Standard Colours : Red, Yellow, Blue, Black and Green (for earthing).
Supplied in 90 metre lengths in attractive cartons. Conform to IS 694:1990. ISI Licence No. CM/L-7829495

* As per IS 3961 (Part-V)-1968

THE ABOVE DATA IS INDICATIVE AND MAY BE REVISED WITHOUT PRIOR INFORMATION.
"POLYCAB" WILL NOT BE LIABLE FOR ANY DAMAGES ARISING OUT OF INCORRECT APPLICATION.



POLYCAB WIRES PVT. LTD.

Polycab House, 771, Mogul Lane, Mahim (W), Mumbai 400 016, India.

Tel.: +91 22 2432 7070-74 • Fax: +91 22 2432 7075

E-Mail : info@polycab.com • www.polycab.com

BUY POLYCAB BUY PEACE OF MIND

Satish Enterprise Pvt. Ltd.

Authorised Distributors



Sales Off:

301, Elphinstone House,
Opp. Sterling Cinema,
17, Murzban Road,
Mumbai - 400 001



022 2207 8520 / 6434/ 35



99207 23289



022 2207 1469

E-mail:

office@satishent.com /
satishent@mtnl.net.in